



















Obelisk Line		Price CHF
Obelisk Si integrated amplifier	<ul style="list-style-type: none"> • Frequency response: 10Hz - 60kHz • Input impedance: 10kOhm • Input sensitivity: 500mV • SNR (A-weighted): 96dB • Max. consumption: 160W • Weight: 6kg • Dimensions (WxHxD): 22x8.5x36cm 	 <p>Black 2'170.00</p>
Obelisk X2 power supply	<ul style="list-style-type: none"> • a dual-mono power amp PSU for Obelisk Si 	 <p>Black 1'230.00</p>
Obelisk PRE pre amplifier	<ul style="list-style-type: none"> • Frequency response: 1Hz – 220kHz • Input impedance: 10kOhm • Output impedance: < 35Ohm • Headroom: 20dB • Max. power consumption: 10W • Weight: 4.2kg 	 <p>Black 2'290.00</p>
Obelisk PS stereo power amplifier	<ul style="list-style-type: none"> • Frequency response: 7Hz - 60kHz • Input impedance: 22kOhm • Input sensitivity: 700mV • Max. consumption: 300W • Weight: 6kg • Dimensions (WxHxD): 22x8.5x32.5cm 	 <p>Black 2'290.00</p>
Obelisk PM mono power amplifier	<ul style="list-style-type: none"> • Frequency response: 6Hz - 60kHz • Input impedance: 22kOhm • Input sensitivity: 700mV • Max. consumption: 300W • Weight: 6.9kg • Dimensions (WxHxD): 22x8.5x32.5cm 	 <p>Black 2'510.00</p>
Obelisk PX power supply	<ul style="list-style-type: none"> • Power supply for Obelisk PRE 	 <p>Black 1'490.00</p>
Obelisk DT + RC CD/HDCD transport	<ul style="list-style-type: none"> • Supported disc types: CD-DA, CD-R, CD-RW • Supported audio formats: CD, HDCD, MP3 • Output format: digital stereo 44.1kHz/16bit S/PDIF • Max. consumption: 15W • Weight: 3.9kg • Dimensions (WxHxD): 22x8.5x32.5cm 	 <p>Black 2'290.00</p>

Obelisk DA d/a converter	<ul style="list-style-type: none"> • Input format: Max 192kHz/24bit S/PDIF • Input format (optical): Max 192kHz/24bit TOSLINK • Input format (USB): Max 48kHz USB Audio 1.1 • Frequency response (+/-0.2dB, 44.1kHz): 3Hz - 21kHz • Max. consumption: 15W • Weight: 4kg • Dimensions (WxHxD): 22x8.5x32.5cm 		Black	2'190.00
Modular line				Price CHF
Canamp headphone amplifier	<ul style="list-style-type: none"> • line level output rca output • sensitivity: 200 mV • impedance: 10 kOhm • signal to noise ratio: 85 dB (unweighted) 		Black	620.00
Dactilus 2 d/a converter	<ul style="list-style-type: none"> • Input format (RCA): Max 192kHz/24bit S/PDIF • Input format (TOSLINK) Max 96kHz/24bit S/PDIF • Frequency response: 3Hz - 21kHz • Maximum output level (0dB): 1.21Vrms • Channel separation: 90dB • Dimensions (WxHxD): 9.5x7.2x25cm 		Black	590.00
Dactilus 3 d/a converter	<ul style="list-style-type: none"> • Input format (RCA): Max 192kHz/24bit S/PDIF • Input format (TOSLINK) Max 96kHz/24bit S/PDIF • Frequency response: 3Hz - 21kHz • Maximum output level (0dB): 1.21Vrms • Channel separation: 90dB • Dimensions (WxHxD): 9.5x7.2x25cm 		Black	750.00
Dactilus 3 + Q-PSU d/a converter	<ul style="list-style-type: none"> • Input format (RCA): Max 192kHz/24bit S/PDIF • Input format (TOSLINK) Max 96kHz/24bit S/PDIF • Frequency response: 3Hz - 21kHz • Maximum output level (0dB): 1.21Vrms • Channel separation: 90dB • Dimensions (WxHxD): 9.5x7.2x25cm 		Black	1'210.00
Orbit 2 turntable power supply	<ul style="list-style-type: none"> • Turntable power supply 		Black	600.00
Quasar MM and MC phono stage	<ul style="list-style-type: none"> • Comes with separate power supply • MM input sensitivity: 3 mV • MC input sensitivity: 0.1 / 0.22 / 0.6 mV • MC input impedance: 100 / 220 / 470 / 47k Ohms • "Low Out" output: 220 mV / 100 Ohm • "High Out" output: 775 mV / 22 Ohm 		Black	1'310.00

Questar MM or MC phono stage	<ul style="list-style-type: none"> • Input: 3 mV/47 kOhm (Questar MM) • Input: 220 uV / 100Ohm (Questar MC) • Frequency range: 20 Hz - 20 kHz/ 0,3 dB • Gain: 42 dB (Questar MM) / 64 dB (Questar MC) • Headroom: 20 dB (Questar MM) • 18 dB (Questar MC) 		Black	510.00
Canopus II Mono	<ul style="list-style-type: none"> • Input sensitivity/impedance: 500 mV/10 kOhm • Power output (20Hz-20kHz): 40/60 W (8/4 Ohm) • Signal/noise ratio (unweighted): 100 dB • Distortion (THD, 1kHz, 1W, 8 Ohm): 0,03% • Frequency range (with filter): 4 Hz-60 kHz (±1 dB) 		Black	660.00
Q-PSU power supply	<ul style="list-style-type: none"> • power Supply for Questar 		Black	510.00

Speaker	Price CHF
----------------	------------------

Enigma 5	<ul style="list-style-type: none"> • 2-way non-directional TMR loudspeaker • Power Handling: 20-100 W • Impedance: 8 Ohm <p>(various real-wood finishes available)</p>		Cherry	3'490.00
			Birch	3'490.00
			Beech	3'490.00
			Walnut	3'690.00

Plug in Cards

Vinyl-1	MM Phono Module (Plug-in card for Obelisk Si / PRE)	230.00
Dactil-1.2	Enhanced D/A Converter Module (Plug-in card for Obelisk Si / PRE / Dactilus / Canalot)	460.00

Garantie 2 Jahre ab Verkauf: Elektronik und Aktiv Lautsprecher

Garantie 3 Jahre ab Verkauf: Passiv Lautsprecher

6 Jahre volle Garantie! - SOLID Garantieverlängerung - fragen Sie uns!

Preisänderungen vorbehalten / Diese Preisliste ersetzt alle vorhergehenden.

Garantie 2 ans à compter de la vente: les appareils électroniques et enceintes acoustique actives

Garantie 3 ans à compter de la vente: enceintes acoustique passives

Garantie totale durant 6 ans! - extension de garantie SOLID - demandez-nous!

Sous réserve de modifications de prix / Cette liste de prix remplace toutes les précédentes.