





YT - line				Price CHF
<b>YT201</b>	Frequency Response: 20 Hz to 20 kHz at -3 dB, Sensitivity: 6dBu, Channel Separation at 1 kHz : 40 dB, Power Consumption: 60 mA (14 W), Maximum Distortion: 0.3%, FI Rejection: 80 dB, Number of Outputs: 1. WxHxD: 39x39x13cm		Black	1'190.00
G - line				Price CHF
<b>GA20 Power AMP</b>	2x220W stereo integre, 720W Bridge mono mode, 2 speaker out, 1 RCA inputs+1 balanced inputs(mono channel), IRIN+UPGRADE PORT, Oversized high quality R-Core transformer (880Va), Full funktion remote control. WxHxD: 43x54.1x14cm		Black	4'290.00
<b>GC10 CD Player</b>	High end CDP for impressive CD, CD-R and CD-RW playback, Wolfson 8740 DAC, Ultra Low Jitter design, RCA and coaxial outputs, IR IN&OUT+UPGRADE PORT, Oversized high quality R-Core transformer, Full function remote control. WxHxD: 43x32,4x9,8cm		Black	1'990.00
<b>GC20 CD Player</b>	High end CDP for impressive CD, CD-R and CD-RW playback, Wolfson 8740 DAC, 24/192 Upsampling, Ultra Low Jitter design, RCA+balanced+coaxial outputs, IR IN&OUT+UPGRADE PORT, 2 Linear power supply, with high quality R-Core transformer, Full function remote control. WxHxD: 43x34.6x14cm		Black	2'390.00
<b>GIA10 Integrate AMP</b>	2x100W stereo integre, 7 RCA inputs + RCA preout + 1 speaker out, IR IN&OUT+UPGRADE PORT, Oversized high quality R-Core tranformer (320 Va), Full function remote control. WxHxD: 43x32.4x9.8cm		Black	2'290.00
<b>GIA20 Integrate AMP</b>	2x150W stereo integre, 6 RCA inputs + 1 balanced input, IR IN&OUT+UPGRADE PORT, Oversized high quality R-Core transformer (620 Va), Full function remote control. WxHxD: 43x34.6x14cm		Black	3'190.00
<b>GP20 PRE-AMP</b>	GAIN + 12dB, 6 RCA inputs + 1 balanced input, 2 line outputs + 1 balanced output + 1 tape output, IR IN&OUT+UPGRADE PORT, 2 Linear power supply with high quality R-Core transformer, Full function remote control. WxHxD: 43x34.6x14cm		Black	1'990.00



W - line			Price CHF
<b>WA202</b> <b>Stereo AMP</b>	<p>AUDIO OUTPUTS: 1 pair of speaker outputs, 1 preout (RCA),            POWER OUTPUT: (8.) 50W per channel, SNR: .90dB,            FREQUENCY RESPONSE: 20Hz-20kHz, THD+N: (20Hz-20kHz)            0.01%, INPUTS: 4 RCA inputs, TUNER BANDS: AM, FM, TUNER            MEMORIES: 40 in FM, 40 in AM, USB POWER SUPPLY: Type B,            5V, 600 mA maximum, POWER SUPPLY: Linear power supply            with high performance EI type transformer. 160 VA, CUSTOM            INSTALLATION IR IN, IR OUT, CONSTRUCTION: Single frame            aluminium.            WxHxD: 32x28x11cm</p>		Black 1'990.00
<b>WM202</b> <b>CD Player</b>	<p>AUDIO OUTPUTS: Gold plated RCA, S/PDIF (coaxial), OUTPUT            LEVEL: (RMS) 2V, SNR (RCA): 107dB, FREQUENCY RESPONSE:            20Hz-20kHz, THD+N (20Hz-20kHz): 0.001%, INPUTS: USB, Optical,            DRIVE COMPATIBILITY: CD, CD-R, CD-RW, D/A CONVERTER:            Texas Instruments PCM1796 (24 bits / 192kHz capable),            DIGITAL INPUT WORD LENGTH: 16, 18, 20 or 24 bits, DIGITAL            INPUT FREQUENCY: 32kHz, 44.1kHz, 48kHz, 88.2kHz, 96kHz,            192kHz, POWER SUPPLY: Linear power supply with high            performance R-Core transformer, CUSTOM INSTALLATION IR            IN, IR OUT, CONSTRUCTION: Single frame aluminium.            WxHxD: 32x28x11cm</p>		Black 1'590.00
<b>WD202</b> <b>DAC</b>	<p>DAC Chip: Texas Instruments PCM1796, Word lengths            accepted (S/PDIF or AES in): 16, 18, 20, or 24 bits, Frequencies            Accepted (S/PDIF or AES in): 32kHz, 44.1kHz, 48kHz, 88.2kHz,            96kHz, and 192kHz, Fixed upsampling: 24 bits/192 kHz, SNR -            120 dB (XLR) / -117dB (RCA), THD+N (20Hz-20KHz) 0.001%,            Frequency Response: 20Hz-20KHz, Output Level (RCA):            Variable, max 2V, Output Level (XLR): Variable, max 4V,            Headphone Output: Variable volume control. Jack format            1/4" (6,3mm), Linear power supply and use of a highly            efficient R-Core transformer, Chassis Construction:            Aluminium, Ultra low jitter design. High precision reclocking,            Inputs: USB, Coaxial, S/Pdif, AES/EBU.            WxHxD: 32x28x6.2cm</p>		Black 1'590.00

<b>iDW1 iPod Dock</b>	<p>AUDIO OUTPUT: Gold plated RCA, VIDEO OUTPUT: Composite video, CUSTOM INSTALLATION IR IN, OUTPUT LEVEL: (RCA) 1.5V, POWER SUPPLY: Optional USB power adapter (1A), via USB connection to a Mac/PC, or via USB connection to a compatible YBA DESIGN amplifier, CONSTRUCTION: Single frame aluminium, COMPATIBILITY iPod nano (1st, 2nd, 3rd and 4th generation), iPod (4th generation, photo and 5th generation), iPod mini, iPod classic, iPod touch (1st and 2nd generation), iPhone, iPhone 3G and 3Gs (flight mode recommended). WxHxD: 11x10.6x6.2cm</p>		Black	419.00
-----------------------	---	--	-------	--------

Interconnect Cable (RCA or XLR)	Price CHF	
<b>Glass</b>	1.23m	380.00
	2.46m	450.00
	3.69m	520.00
<b>Diamond</b>	1.23m	820.00
	2.46m	1'270.00
	3.69m	1'690.00

Speaker Cable	Price CHF	
<b>Glass</b>	2.46m	380.00
	3.69m	450.00
	4.92m	520.00
<b>Diamond</b>	2.46m	1'080.00
	3.69m	1'530.00
	4.92m	1'920.00
<b>Diamond</b>	Roll/50m	8'070.00

AC Cable	Price CHF	
<b>Diamond</b>	1.23m	580.00

Garantie 2 Jahre ab Verkauf: Elektronik und Aktiv Lautsprecher  
 Garantie 3 Jahre ab Verkauf: Passiv Lautsprecher  
 6 Jahre volle Garantie! - SOLID Garantieverlängerung - fragen Sie uns!  
 Preisänderungen vorbehalten / Diese Preisliste ersetzt alle vorhergehenden.

Garantie 2 ans à compter de la vente: les appareils électroniques et enceintes acoustique actives  
 Garantie 3 ans à compter de la vente: enceintes acoustique passives  
 Garantie totale durant 6 ans! - extension de garantie SOLID - demandez-nous!  
 Sous réserve de modifications de prix / Cette liste de prix remplace toutes les précédentes.